


PP-YB or AL-YB, NONWOVEN/ ALUMINUM FOIL-REINFORCED BUTYL TAPE



DESCRIPTION

MAROF LINE PP-YB or AL-YB is a polypropylene nonwoven fabric or aluminum foil-reinforced butyl rubber-based self-adhesive insulation tape.



- 150 mm:
In a box (6 Rolls, Each Roll 10 mt) 60 mt

PRODUCT CODE



1. MAROF LINE PP-YB 100 :Nonwoven Reinforced 100 mm
2. MAROF LINE PP-YB 150 :Nonwoven Reinforced 150 mm
3. MAROF LINE AL-YB 100 :Aluminium Reinforced 100 mm
4. MAROF LINE AL-YB 150 :Aluminium Reinforced 150 mm

FIELDS OF USAGE



- For sealing purposes in the construction industry.
- As a sound and vibration absorber in the automotive and white goods industry,
- For air tightness in ventilation ducts.
- For waterproofing in modular metal water tanks.
- At the joints and ends of curtain wall panels.

ADVANTAGES



- It adapts to all known material surfaces very well.
- In addition to good compatibility with metals, concrete, wall, wood, glass, rigid PVC, bituminous, paint systems, it enables a wide variety of combinations in sealing systems thanks to its very good adhesion.
- It has high resistance to UV rays, bad weather conditions and water.
- It can be used in both indoor and outdoor places.
- It is impermeable to vapor diffusion.
- It provides coverage on its own, no need for additional materials.
- Compatible on plexiglass and macrolon.



CAUTION

- Floor and ambient temperature and humidity should be taken into account in applications made in open and closed spaces.

TECHNICAL SPECIFICATIONS



Chemical composition	Butyl Rubber
Colour	Grey
Thickness	1 mm
Width	100 – 150 mm
Density	1 – 1.2 gr/cm ²
Water Absorption	Negligible.
Application temperature	+5 - +30 °C
Temperature Resistance	-40 - + 120 °C
Resistance to chemicals	High
Resistance to external environment	High

PREPARING THE SURFACE FOR APPLICATION



- Application surfaces should be dry, clean and free from free particles.

APPLICATION



- The application surfaces are determined and appropriate tape lengths are prepared. The silicone paper is removed and the material is adhered to the surface. It is pressed with a roller to ensure perfect adhesion.

SHELF LIFE AND STORAGE



- 12 months as unopened under suitable storage conditions (in a dry and cool environment, in its original packaging).
- 100 mm:
In a box (12 Rolls, Each Roll 10 mt) 120 mt



CAUTION

MAROF YAPI is not responsible for any defects or errors that may arise if the product is used on a surface or for properties other than described above.