



DESCRIPTION

MİMCONTACT is an acrylic copolymer-based pink-pigmented primer with a surface-filling characteristic. It can be used as a primer on concrete surfaces with high water absorbency to increase adherence and working time.

FIELDS OF USAGE

- It is used on concrete surfaces with high water absorption.
- It is used on the surfaces of plaster-based ceilings and walls.
- It is used on surfaces that will be covered with ceramic or tile.

ADVANTAGES

- Ensures good adhesion of plaster, ceramics or similar materials by providing a mineral layer on the applied surface.

PREPARING THE SURFACE FOR APPLICATION

- The application surface must be fully cleaned off dust, rust, mud and oil.
- Before applying on silicone-based painted floors, the floor must be made rough.
- The product should be mixed before use.
- It is applied as a single coat.
- It is ready application, no need for extra water.

CONSUMPTION

- 1 m² consumption: 0,350 kg/m² to 0,500 kg/m²

TOOL CLEANING

- Brushes and similar tools can be cleaned with plenty of water.

SHELF LIFE AND STORAGE

- A maximum of three buckets are stacked on top of each other.
- Products should be stored in a cool and covered environment.
- Shelf life is at least 18 months under proper storage conditions.

PACKAGING

- 12 kg. plastic bucket

COLOUR

- Pink

CAUTION

- Do not apply without mixing,
- Apply at temperatures between 5°C-30°C.
- Apply with brush or roller.

QUALITY STANDARDS

TS EN 1504-2

CAUTION

MAROF YAPI is not responsible for any defects or errors that may arise if the product is used on a surface or for properties other than described above.